

Designer Series Faucets



Polished
Chrome

Satin
Nickel

White

Biscuit

Polished
Brass

Antique
Bronze

Black

Bright
Nickel

Venetian
Bronze

Brushed
Stainless

Features:

- Air gap
- Smooth operating ceramic disk element with Lever style handle
- 12" High neck swivels 360° has spout reach of 5" with protective tip to prevent after drip
- Patented modular air gap (U.S. patent #7,011,106)
- Base diameter is 2-1/4" (57 mm)
- Flow rate: 1.0 gpm/3.785 lpm at 35 PSI
- 1/4" OD x 30" tubing pre-installed
- Certified to NSF/ANSI Standard 61 – Annex G
- Compliant with California's Health and Safety Code (Section 116875 known as AB1953)
- Includes installation hardware and instructions

*Limited Stock

905 Value Series Faucets



Polished
Chrome

Satin
Nickel

White

Bright
Golden

Antique
Brass

Black
Matte

Antique
Wine

Bright
Black

Antique
Bronze

Oil Rubbed
Bronze

Features:

- Air gap
- 1/4-turn ceramic disk valve, engineered plastic housing
- Faucet height varies with faucet style; Spout reach approximately 5-1/2"
- Lead-free brass gooseneck spout swivels 360 degrees
- Lead-free plastic water passage with plated zinc alloy outer body
- Flow rate: 1.0 gpm/3.785 lpm at 35 PSI
- 1/4" OD x 36" tubing pre-installed
- Certified to NSF/ANSI Standard 61 Section 9-G
- Includes installation hardware and instructions

888 Value Series Faucets



Polished
Chrome

Antique
Wine

White

Black

Satin
Nickel

Antique
Brass

Black
Matte

Antique
Bronze

Bright
Gold

Oil Rubbed
Bronze

Features:

- Air gap
- 1/4-turn ceramic disk valve, engineered plastic housing
- Faucet height varies with faucet style; Spout reach approximately 5-1/2"
- Lead-free brass gooseneck spout swivels 360 degrees
- Lead-free plastic water passage with plated zinc alloy outer body
- Flow rate: 1.0 gpm/3.785 lpm at 35 PSI
- 1/4" OD x 36" tubing pre-installed
- Certified to NSF/ANSI Standard 61 Section 9-G
- Includes installation hardware and instructions

803 Value Series Faucets



Polished
Chrome

Satin
Nickel

Features:

- Air gap
- 1/4-turn ceramic disk valve, engineered plastic housing
- Faucet height varies with faucet style; Spout reach approximately 5-1/2"
- Lead-free brass gooseneck spout swivels 360 degrees
- Lead-free plastic water passage with plated zinc alloy outer body
- Flow rate: 1.0 gpm/3.785 lpm at 35 PSI
- 1/4" OD x 36" tubing pre-installed
- Certified to NSF/ANSI Standard 61 Section 9-G
- Includes installation hardware and instructions

Top Mount Series Faucets



Brushed Nickel Chrome White

Features:

- Top Mount
- Quarter turn on/off
- Air gap
- Available with or without quality monitor
 - Quality monitor requires comparator board on manifold
 - Faucet without quality monitor base is compatible with all drinking water systems
- Meets NSF/ANSI Standards 61/372, material and structural integrity requirements of NSF/ANSI Standards 42 or 58
- Includes $\frac{3}{8}$ " faucet connector
- Includes hardware and installation instructions